

VE-221-MX-F3 Information

Heisener.com

Part Number VE-221-MX-F3
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 12V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-221-MX-F3 Specifications

Manufacturer Part Number VE-221-MX-F3 Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs I Voltage - Input (Min) 21V Voltage - Input (Max) Voltage - Output 1 12V Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Fower (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Features For a Power Weith Isolation Through Hole Features Features Through Hole Features Features Time Commercial Isolation Features Through Hole Features Through Hole Features Through Hole Features Temperature Features Through Hole Features Through Hole Features Temperature Through Hole Features Through Hole		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 56V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Manufacturer Part Number	VE-221-MX-F3
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 56V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 56V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Output (Max) 56V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 21 V Voltage - Input (Max) 56 V Voltage - Output 1 12 V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25 A Power (Watts) 75 W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Series	VE-200
Voltage - Input (Min) 21V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Type	Isolated Module
Voltage - Input (Max) 56V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Number of Outputs	1
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Input (Min)	21V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Input (Max)	56V
Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Output 2	-
Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Output 3	-
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Output 4	-
Voltage - Isolation3kV (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature-55°C ~ 85°CEfficiency90%Mounting TypeThrough Hole	Current - Output (Max)	6.25A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Power (Watts)	75W
Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Isolation	3kV (3000V)
Operating Temperature -55°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 90% Mounting Type Through Hole	Features	OCP, OTP, OVP, SCP
Mounting Type Through Hole	Operating Temperature	-55°C ~ 85°C
	Efficiency	90%
Dockage / Case Full Brick	Mounting Type	Through Hole
rackage / Case Full Dick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	Size / Dimension	4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-221-MX-F3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-221-MX-F3 Payment Methods


































If you have any question about VE-221-MX-F3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com