

VE-24X-CW-F4 Information

Heisener.com

VE-24X-CW-F4 Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 5.2V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-24X-CW-F4 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Voltage - Isolation Applications VE-24X-CW-F4 Vicor Corporation Vicor Corporation Vole-24X-CW-F4 Vicor Corporation 100	
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Number of Outputs 1 Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Min) 55V Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Max) 100V Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Output 1 5.2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Output 4 - Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Current - Output (Max) 19.23A Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Power (Watts) 100W Voltage - Isolation 3kV (3000V)	
Voltage - Isolation 3kV (3000V)	
Applications ITE (Commercial)	
112 (00111111111111111111111111111111111	
Features OCP, OTP, OVP, SCP	
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

VE-24X-CW-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-24X-CW-F4 Payment Methods



















VE-24X-CW-F4 Shipping Methods













If you have any question about VE-24X-CW-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com