

## **VE-25X-EY-F2 Information**

Heisener.com

**Part Number** VE-25X-EY-F2 **Manufacturer** Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 5.2V 50W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VE-25X-EY-F2 Specifications**

Manufacturer Part Number         VE-25X-EY-F2           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%           Movetics Tense         The Expect Material		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Manufacturer Part Number	VE-25X-EY-F2
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Manufacturer	Vicor Corporation
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Category	Power Supplies - Board Mount
Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       100V         Voltage - Input (Max)       200V         Voltage - Output 1       5.2V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       9.62A         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C         Efficiency       88%	Series	VE-200
Voltage - Input (Min)         100V           Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Туре	Isolated Module
Voltage - Input (Max)         200V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         9.62A           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C           Efficiency         88%	Number of Outputs	1
Voltage - Output 1       5.2V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       9.62A         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C         Efficiency       88%	Voltage - Input (Min)	100V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       9.62A         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C         Efficiency       88%	Voltage - Input (Max)	200V
Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       9.62A         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C         Efficiency       88%	Voltage - Output 1	5.2V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -10°C ~ 85°C  Efficiency  88%	Voltage - Output 2	-
Current - Output (Max) $9.62A$ Power (Watts) $50W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)Features $OCP, OTP, OVP, SCP$ Operating Temperature $-10^{\circ}C \sim 85^{\circ}C$ Efficiency $88\%$	Voltage - Output 3	-
Power (Watts) 50W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -10°C ~ 85°C  Efficiency 88%	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency $88\%$	Current - Output (Max)	9.62A
Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -10°C ~ 85°C  Efficiency 88%	Power (Watts)	50W
Features OCP, OTP, OVP, SCP  Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency $88\%$	Voltage - Isolation	3kV (3000V)
Operating Temperature -10°C ~ 85°C Efficiency 88%	Applications	ITE (Commercial)
Efficiency 88%	Features	OCP, OTP, OVP, SCP
	Operating Temperature	-10°C ~ 85°C
Manusina Tura	Efficiency	88%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	Size / Dimension	4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VE-25X-EY-F2 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VE-25X-EY-F2 Payment Methods**



















## **VE-25X-EY-F2 Shipping Methods**













If you have any question about VE-25X-EY-F2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com