

VE-26V-CW-F1 Information

Heisener.com

Part Number VE-26V-CW-F1 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 5.8V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-26V-CW-F1 Specifications

Manufacturer Part Number VE-26V-CW-FI Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Manufacturer Part Number	
DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Output (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Series	VE-200
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Туре	Isolated Module
Voltage - Input (Max) 400V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Number of Outputs	1
Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.24A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Input (Min)	200V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Input (Max)	400V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Output 1	5.8V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 100W Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature 17.24A 100W SkV (3000V) ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Output 3	-
Power (Watts) $100W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output (Max)	17.24A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Power (Watts)	100W
Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Isolation	3kV (3000V)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	OCP, OTP, OVP, SCP
Efficiency 90%	Operating Temperature	-25°C ~ 85°C
·	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	Size / Dimension	4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-26V-CW-F1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-26V-CW-F1 Payment Methods



















VE-26V-CW-F1 Shipping Methods













If you have any question about VE-26V-CW-F1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com