

VE-2T4-CX-B1 Information

Heisener.com

VE-2T4-CX-B1 Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 48V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-2T4-CX-B1 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs I Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Vicor Corporation Ve-2T4-CX-B1 Vicor Corporation Ve-2T4-CX-B1 Vicor Corporation Ve-2T4-CX-B1 Vicor Corporation Ve-2T4-CX-B1 Ve-2-20 Ve-2-20	
Power Supplies - Board Mount	
DC DC Converters	
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 66V Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 66V Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 66V Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Number of Outputs 1 Voltage - Input (Min) 66V Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Input (Min) 66V Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Input (Max) 160V Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features 48V	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.56A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Features OCP, OTP, OVP, SCP	
Operating Temperature 25°C ~ 85°C	
Operating reinperature	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

VE-2T4-CX-B1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-2T4-CX-B1 Payment Methods



















VE-2T4-CX-B1 Shipping Methods













If you have any question about VE-2T4-CX-B1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com