

VE-2W1-IY-B1 Information

Heisener.com

Part Number VE-2W1-IY-B1
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 12V 50W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-2W1-IY-B1 Specifications

Manufacturer VE-2W1-IY-B1 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Manufacturer Part Number	VE-2W1-IY-B1
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Series	VE-200
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Type	Isolated Module
Voltage - Input (Max) 36V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Number of Outputs	1
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Voltage - Input (Min)	18V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Voltage - Input (Max)	36V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.17A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Voltage - Output 2	-
Current - Output (Max) $4.17A$ Power (Watts) $50W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Output 3	-
Power (Watts) $50W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Current - Output (Max)	4.17A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90%	Power (Watts)	50W
Features OCP, OTP, OVP, SCP Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Isolation	3kV (3000V)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Applications	ITE (Commercial)
Efficiency 90%	Features	OCP, OTP, OVP, SCP
	Operating Temperature	-40°C ~ 85°C
Mounting Type Through Hole	Efficiency	90%
	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)	Size / Dimension	4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-2W1-IY-B1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-2W1-IY-B1 Payment Methods



















VE-2W1-IY-B1 Shipping Methods













If you have any question about VE-2W1-IY-B1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com