

VE-2WJ-IW-F4 Information

Heisener.com

VE-2WJ-IW-F4 Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 36V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-2WJ-IW-F4 Specifications

Manufacturer VE-2WJ-IW-F4 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Power Supplies - Board Mount	
DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Input (Max) 36V Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.78A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial)	
Current - Output (Max) Power (Watts) Voltage - Isolation Applications 2.78A 100W Voltage - Isolation ITE (Commercial)	
Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Applications ITE (Commercial)	
CCD OTD OVD CCD	
readures OCP, OTP, OVP, SCP	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

VE-2WJ-IW-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-2WJ-IW-F4 Payment Methods



















VE-2WJ-IW-F4 Shipping Methods













If you have any question about VE-2WJ-IW-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com