

VE-B00-CX-F3 Information

Heisener.com

Part Number VE-B00-CX-F3 **Manufacturer** Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 5V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-B00-CX-F3 Specifications

Manufacturer Part Number VE-B00-CX-F3 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Manufacturer Part Number	VE-B00-CX-F3
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Series	VE-200
Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Туре	Isolated Module
Voltage - Input (Max) 20V Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature 5V	Voltage - Input (Min)	10V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Input (Max)	20V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 75W Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C	Voltage - Output 3	-
Power (Watts) $75W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output (Max)	15A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Power (Watts)	75W
Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Isolation	3kV (3000V)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	OCP, OTP, OVP, SCP
Efficiency 90%	Operating Temperature	-25°C ~ 85°C
Differency 70/0	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	Size / Dimension	4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-B00-CX-F3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-B00-CX-F3 Payment Methods



















VE-B00-CX-F3 Shipping Methods













If you have any question about VE-B00-CX-F3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com