



VE-B0B-IX-B1 Information

Heisener.com

VE-B0B-IX-B1 Part Number Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 95V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-B0B-IX-B1 Specifications

Manufacturer Part Number VE-B0B-IX-B1 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Manufacturer Part Number	VE-B0B-IX-B1
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Series	VE-200
Voltage - Input (Min) 10V Voltage - Output (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Туре	Isolated Module
Voltage - Input (Max) 20V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Number of Outputs	1
Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Input (Min)	10V
Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type	Voltage - Input (Max)	20V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency Mounting Type Through Hole	Voltage - Output 1	95V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency Mounting Type Through Hole	Voltage - Output 2	-
Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole	Voltage - Output 3	-
Power (Watts) $75W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency90%Mounting TypeThrough Hole	Voltage - Output 4	-
Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency90%Mounting TypeThrough Hole	Current - Output (Max)	790mA
ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency90%Mounting TypeThrough Hole	Power (Watts)	75W
Features OCP, OTP, OVP, SCP Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90% Mounting Type Through Hole	Voltage - Isolation	3kV (3000V)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90% Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 90% Mounting Type Through Hole	Features	OCP, OTP, OVP, SCP
Mounting Type Through Hole	Operating Temperature	-40°C ~ 85°C
	Efficiency	90%
Package / Case Full Brick	Mounting Type	Through Hole
	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)	Size / Dimension	4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-B0B-IX-B1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-B0B-IX-B1 Payment Methods



















VE-B0B-IX-B1 Shipping Methods













If you have any question about VE-B0B-IX-B1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com