



### **VE-B2H-CY-S Information**

Heisener.com

Part Number VE-B2H-CY-S
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 52V 50W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VE-B2H-CY-S Specifications**

Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C - 85°C           Efficiency         90%           Mounting Type         Through Hole	Manufacturer Part Number	VE-B2H-CY-S
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Manufacturer	Vicor Corporation
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Category	Power Supplies - Board Mount
Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         21V           Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       21V         Voltage - Input (Max)       56V         Voltage - Output 1       52V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       962mA         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -25°C ~ 85°C         Efficiency       90%         Mounting Type       Through Hole	Series	VE-200
Voltage - Input (Min)         21V           Voltage - Output (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Type	Isolated Module
Voltage - Input (Max)         56V           Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Number of Outputs	1
Voltage - Output 1         52V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         962mA           Power (Watts)         50W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole	Voltage - Input (Min)	21V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       962mA         Power (Watts)       50W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -25°C ~ 85°C         Efficiency       90%         Mounting Type       Through Hole	Voltage - Input (Max)	56V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  Features  OCP, OTP, OVP, SCP  Operating Temperature  Efficiency  Mounting Type	Voltage - Output 1	52V
Voltage - Output 4  Current - Output (Max) 962mA  Power (Watts) 50W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%  Mounting Type Through Hole	Voltage - Output 2	-
Current - Output (Max) 962mA  Power (Watts) 50W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%  Mounting Type Through Hole	Voltage - Output 3	-
Power (Watts) $50W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency $90\%$ Mounting TypeThrough Hole	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency90%Mounting TypeThrough Hole	Current - Output (Max)	962mA
Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%  Mounting Type Through Hole	Power (Watts)	50W
Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%  Mounting Type Through Hole	Voltage - Isolation	3kV (3000V)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90% Mounting Type Through Hole	Applications	ITE (Commercial)
Efficiency 90% Mounting Type Through Hole	Features	OCP, OTP, OVP, SCP
Mounting Type Through Hole	Operating Temperature	-25°C ~ 85°C
	Efficiency	90%
Pagkaga / Casa Full Prigk	Mounting Type	Through Hole
rackage / Case Full Dilck	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)	Size / Dimension	4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VE-B2H-CY-S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VE-B2H-CY-S Payment Methods**



















## **VE-B2H-CY-S Shipping Methods**













If you have any question about VE-B2H-CY-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com