



VE-B5N-CX-S Information

Heisener.com

Part Number VE-B5N-CX-S Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 18.5V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-B5N-CX-S Specifications

Manufacturer VE-B5N-CX-S Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Input (Max) 200V Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 1 18.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.05A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications - Applications - Current - Output (Max) 4.05A 75W Voltage - Isolation ITE (Commercial)	
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial)	
Current - Output (Max) Power (Watts) Voltage - Isolation Applications 4.05A 75W Voltage - Isolation ITE (Commercial)	
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)	
Applications ITE (Commercial)	
COR OWN CAN COR	
Features OCP, OTP, OVP, SCP	
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

VE-B5N-CX-S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-B5N-CX-S Payment Methods



















VE-B5N-CX-S Shipping Methods













If you have any question about VE-B5N-CX-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com