

VE-B72-EY-F4 Information

Heisener.com

Part Number VE-B72-EY-F4 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 15V 50W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-B72-EY-F4 Specifications

Manufacturer Part Number VE-B72-EY-F4 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Through Hole		
Power Supplies - Board Mount	Manufacturer Part Number	VE-B72-EY-F4
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Category	Power Supplies - Board Mount
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Series	VE-200
Voltage - Input (Min) 100V Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Type	Isolated Module
Voltage - Input (Max) 375V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Number of Outputs	1
Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.33A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Voltage - Input (Min)	100V
Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency	Voltage - Input (Max)	375V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Efficiency 88%	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Efficiency 88%	Voltage - Output 3	-
Power (Watts) $50W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 88%	Voltage - Output 4	-
Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 88%	Current - Output (Max)	3.33A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -10°C ~ 85°C Efficiency 88%	Power (Watts)	50W
Features OCP, OTP, OVP, SCP Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 88%	Voltage - Isolation	3kV (3000V)
Operating Temperature -10°C ~ 85°C Efficiency 88%	Applications	ITE (Commercial)
Efficiency 88%	Features	OCP, OTP, OVP, SCP
	Operating Temperature	-10°C ~ 85°C
Mounting Type Through Hole	Efficiency	88%
	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	Size / Dimension	4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VE-B72-EY-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-B72-EY-F4 Payment Methods



















VE-B72-EY-F4 Shipping Methods













If you have any question about VE-B72-EY-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com