



#### **VE-BTX-EV-F1 Information**

Heisener.com

Part Number VE-BTX-EV-F1 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 5.2V 150W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VE-BTX-EV-F1 Specifications**

Manufacturer Part Number         VE-BTX-EV-F1           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         28.85A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         5.2V           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         28.85A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C	Manufacturer Part Number	VE-BTX-EV-F1
DC DC Converters	Manufacturer	Vicor Corporation
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         28.85A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C	Category	Power Supplies - Board Mount
Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         28.85A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C		DC DC Converters
Type       Isolated Module         Number of Outputs       1         Voltage - Input (Min)       66V         Voltage - Input (Max)       160V         Voltage - Output 1       5.2V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       28.85A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C	ackage	Full Brick
Number of Outputs       1         Voltage - Input (Min)       66V         Voltage - Input (Max)       160V         Voltage - Output 1       5.2V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       28.85A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C	eries	VE-200
Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         5.2V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         28.85A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -10°C ~ 85°C	ype	Isolated Module
Voltage - Input (Max)       160V         Voltage - Output 1       5.2V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       28.85A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -10°C ~ 85°C	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  Features  OCP, OTP, OVP, SCP  Operating Temperature  5.2V  5.2V  5.2V  5.2V  5.2V  Current - Output 2  - Current - Output 3  - Current - Output (Max)  - Current - Output (Max)  150W  Voltage - Isolation  3kV (3000V)  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  -10°C ~ 85°C	Voltage - Input (Min)	66V
Voltage - Output 2  Voltage - Output 3  -  Voltage - Output 4  -  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -10°C ~ 85°C	Voltage - Input (Max)	160V
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  Features  OCP, OTP, OVP, SCP  Operating Temperature  -10°C ~ 85°C	Voltage - Output 1	5.2V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -10°C ~ 85°C	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  150W  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  28.85A  150W  150W  OCP, OTP, OVP, SCP  -10°C ~ 85°C	Voltage - Output 3	-
Power (Watts) $150W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output (Max)	28.85A
Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Power (Watts)	150W
Features OCP, OTP, OVP, SCP Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Oltage - Isolation	3kV (3000V)
Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	ITE (Commercial)
	eatures	OCP, OTP, OVP, SCP
TCC .	Operating Temperature	-10°C ~ 85°C
Efficiency 88%	Efficiency	88%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	lize / Dimension	4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VE-BTX-EV-F1 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VE-BTX-EV-F1 Payment Methods**



















## **VE-BTX-EV-F1 Shipping Methods**













If you have any question about VE-BTX-EV-F1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com