



VE-LU1-IW Information

Heisener.com

For Reference Only

Part Number VE-LU1-IW

Manufacturer Vicor Corporation

Category

Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description

AC/DC POWER SUPPLY 12V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-LU1-IW Specifications

Manufacturer Part Number VE-LUI-IW Manufacturer Vicor Corporation Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series FlatPAC? Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	_	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series FlatPAC? Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Manufacturer Part Number	VE-LU1-IW
Package - Series FlatPAC? Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Manufacturer	Vicor Corporation
Package - Series FlatPAC? Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FlatPAC? Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Series	FlatPAC?
Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Type	Enclosed
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature -30°C ~ 85°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max)	Voltage - Input	90 ~ 132 VAC, 180 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature -30°C ~ 85°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Voltage - Output 2	-
Current - Output (Max) 8.33A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 8.33A 100W Adjustable Output Size / Dimension 8.33A 100W Adjustable Output Size / S	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 100W 4.242kV (4242V) 4.242kV (4242V) 50% Chassis Mount 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Current - Output (Max)	8.33A
Voltage - Isolation 4.242kV (4242V) Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Power (Watts)	100W
Efficiency 90% Operating Temperature -30°C ~ 85°C (With Derating) Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Applications	ITE (Commercial)
Operating Temperature -30°C ~ 85°C (With Derating) Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension -30°C ~ 85°C (With Derating) Adjustable Output, Remote Sense Understand Sense Size / Dimension -30°C ~ 85°C (With Derating) Adjustable Output, Remote Sense Size / Dimension -30°C ~ 85°C (With Derating)	Voltage - Isolation	4.242kV (4242V)
Features Adjustable Output, Remote Sense Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Efficiency	90%
Mounting Type Chassis Mount Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Operating Temperature	-30°C ~ 85°C (With Derating)
Size / Dimension 9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)	Features	Adjustable Output, Remote Sense
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	9.25" L x 2.50" W x 1.37" H (234.8mm x 63.5mm x 34.8mm)
		Report errors?

VE-LU1-IW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-LU1-IW Payment Methods



















VE-LU1-IW Shipping Methods













If you have any question about VE-LU1-IW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com