

VEL05US050-EU-MB

VEL05US050-EU-MB Information



For Reference Only

Part Number VEL05US050-EU-MB

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 5W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VEL05US050-EU-MB Specifications

Manufacturer Part Number VEL05US050-EU-MB Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series VEL05 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series VEL05 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Manufacturer Part Number	VEL05US050-EU-MB
Package - Series VEL05 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Manufacturer	XP Power
Package - Series VEL05 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series VEL05 Region Utilized Europe Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1APower (Watts)5WNo Load Power Consumption100mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorUSB MiniSize / Dimension2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Package	-
FormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $1A$ Power (Watts) $5W$ No Load Power Consumption $100mW (Max)$ Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorUSB MiniSize / Dimension $2.17'' \text{ L x } 0.95'' \text{ W x } 2.13'' \text{ H } (55.1mm x } 24.1mm x 54.0mm)$	Series	VEL05
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Region Utilized	Europe
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 90 ~ 264 VAC 5V Current - Output (Max) 1A 5W Level VI Operating Temperature 0°C ~ 60°C USB Mini 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 1A Power (Watts) No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 5V 1A 1A 1A 1A 1A 1D 100mW (Max) 100mW (Max)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 1A 0 C To Commercial (Max) 100mW (Max) 100mW (Max) - 100mW (Max)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 5W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Voltage - Output	5V
No Load Power Consumption 100mW (Max) Polarization - ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Current - Output (Max)	1A
Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB Mini Size / Dimension $2.17^{\circ}\text{L} \times 0.95^{\circ}\text{W} \times 2.13^{\circ}\text{H} (55.1 \text{mm} \times 24.1 \text{mm} \times 54.0 \text{mm})$	Power (Watts)	5W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	No Load Power Consumption	100mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB Mini Size / Dimension $2.17^{\circ}\text{L} \times 0.95^{\circ}\text{W} \times 2.13^{\circ}\text{H} (55.1 \text{mm} \times 24.1 \text{mm} \times 54.0 \text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB Mini Size / Dimension $2.17^{\circ}\text{L x } 0.95^{\circ}\text{W x } 2.13^{\circ}\text{H } (55.1\text{mm x } 24.1\text{mm x } 54.0\text{mm})$	Applications	ITE (Commercial)
Output Connector USB Mini Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Efficiency	Level VI
Size / Dimension 2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	USB Mini
Report errors?	Size / Dimension	2.17" L x 0.95" W x 2.13" H (55.1mm x 24.1mm x 54.0mm)
		Report errors?

VEL05US050-EU-MB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VEL05US050-EU-MB Payment Methods



















VEL05US050-EU-MB Shipping Methods













If you have any question about VEL05US050-EU-MB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com