



VEP36US09 Information



For Reference Only

Part Number VEP36US09 Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 9V 36W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VEP36US09 Specifications

Manufacturer Part NumberVEP36US09ManufacturerXP PowerCategoryPower Supplies - External/Internal (Off-Board) AC DC Desktop, Wall AdaptersPackage-SeriesVEPRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)3APower (Watts)27WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series VEP Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Manufacturer Part Number	VEP36US09
Package - Series VEP Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Manufacturer	XP Power
Package - Series VEP Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesVEPRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)3APower (Watts)27WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 53.0mm)	Series	VEP
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $9V$ Current - Output (Max) $3A$ Power (Watts) $27W$ No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 11.0\text{mm}$ Size / Dimension $4.02^{\circ}\text{L} \text{ x } 1.42^{\circ}\text{ W x } 2.09^{\circ}\text{ H } (102.0\text{mm x } 36.0\text{mm x } 53.0\text{mm})$	Form	Wall Mount
Voltage - Output (Max) 3A Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 27W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Voltage - Output	9V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $4.02^{\circ}\text{L} \times 1.42^{\circ}\text{W} \times 2.09^{\circ}\text{H} (102.0 \text{mm} \times 36.0 \text{mm} \times 53.0 \text{mm})$	Current - Output (Max)	3A
Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Power (Watts)	27W
Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $4.02^{\circ}\text{L} \text{ x } 1.42^{\circ}\text{W} \text{ x } 2.09^{\circ}\text{H} (102.0\text{mm x } 36.0\text{mm x } 53.0\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $4.02^{\circ}\text{L} \text{ x } 1.42^{\circ}\text{W} \text{ x } 2.09^{\circ}\text{H} (102.0\text{mm x } 36.0\text{mm x } 53.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $4.02^{\circ}\text{L} \text{ x } 1.42^{\circ}\text{W} \text{ x } 2.09^{\circ}\text{H} (102.0\text{mm x } 36.0\text{mm x } 53.0\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Efficiency	Level V
Size / Dimension 4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	4.02" L x 1.42" W x 2.09" H (102.0mm x 36.0mm x 53.0mm)
		Report errors?

VEP36US09 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VEP36US09 Payment Methods



















VEP36US09 Shipping Methods













If you have any question about VEP36US09, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com