



## **VEU10US050-US Information**

Part Number VEU10US050-US

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** FIXED PLUG ADAPTER, 10W, USB, LE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VEU10US050-US Specifications**

Manufacturer Part Number         VEU10US050-US           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         VEU10           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade, Multi-Blade (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2.1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         USB A Receptacle           Size / Dimension         1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)           Report errors?			
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesVEU10Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2.1APower (Watts)10WNo Load Power Consumption75mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 60°COutput ConnectorUSB A ReceptacleSize / Dimension1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Manufacturer Part Number	VEU10US050-US	
Package         -           Series         VEU10           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade, Multi-Blade (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2.1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         USB A Receptacle           Size / Dimension         1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Manufacturer	XP Power	
Package         -           Series         VEU10           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade, Multi-Blade (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2.1A           Power (Watts)         10W           No Load Power Consumption         75mW (Max)           Polarization         -           Applications         ITE (Commercial)           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         USB A Receptacle           Size / Dimension         1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesVEU10Region UtilizedNorth AmericaFormWall MountInput TypeFixed Blade, Multi-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2.1APower (Watts)10WNo Load Power Consumption75mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 60°COutput ConnectorUSB A ReceptacleSize / Dimension1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)		AC DC Desktop, Wall Adapters	
Region Utilized  North America  Form  Wall Mount  Input Type Fixed Blade, Multi-Blade (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 2.1A  Power (Watts) 10W  No Load Power Consumption 75mW (Max)  Polarization - Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 60°C  Output Connector USB A Receptacle Size / Dimension  Narth America North America 10W  North America 10W  10W  10W  10W  10W  10W  10W  10W	Package	-	
Form Wall Mount Input Type Fixed Blade, Multi-Blade (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 2.1A  Power (Watts) 10W  No Load Power Consumption 75mW (Max)  Polarization -  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 60°C  Output Connector USB A Receptacle  Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Series	VEU10	
Input Type Fixed Blade, Multi-Blade (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 2.1A  Power (Watts) 10W  No Load Power Consumption 75mW (Max)  Polarization -  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 60°C  Output Connector USB A Receptacle  Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Region Utilized	North America	
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5\text{V}$ Current - Output (Max) $2.1\text{A}$ Power (Watts) $10\text{W}$ No Load Power Consumption $75\text{mW}$ (Max)  Polarization -  Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB A Receptacle  Size / Dimension $1.45^{\circ}$ L x $0.86^{\circ}$ W x $2.00^{\circ}$ H ( $36.8\text{mm}$ x $21.8\text{mm}$ x $50.8\text{mm}$ )	Form	Wall Mount	
Voltage - Output $5V$ Current - Output (Max) $2.1A$ Power (Watts) $10W$ No Load Power Consumption $75mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorUSB A ReceptacleSize / Dimension $1.45$ " L x $0.86$ " W x $2.00$ " H $(36.8mm$ x $21.8mm$ x $50.8mm$ )	Input Type	Fixed Blade, Multi-Blade (Sold Separately)	
Current - Output (Max)  Power (Watts)  10W  No Load Power Consumption  75mW (Max)  Polarization  -  Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 60°C  Output Connector  USB A Receptacle  Size / Dimension  1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Voltage - Input	90 ~ 264 VAC	
Power (Watts)  10W  No Load Power Consumption  75mW (Max)  Polarization  - Applications  ITE (Commercial)  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 60°C  Output Connector  USB A Receptacle  Size / Dimension  1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Voltage - Output	5V	
No Load Power Consumption 75mW (Max)  Polarization -	Current - Output (Max)	2.1A	
Polarization - Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB A Receptacle  Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Power (Watts)	10W	
Applications ITE (Commercial)  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB A Receptacle  Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	No Load Power Consumption	75mW (Max)	
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector USB A Receptacle  Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Polarization	-	
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorUSB A ReceptacleSize / Dimension $1.45^{\circ}\text{L x } 0.86^{\circ}\text{W x } 2.00^{\circ}\text{H } (36.8 \text{mm x } 21.8 \text{mm x } 50.8 \text{mm})$	Applications	ITE (Commercial)	
Output Connector USB A Receptacle Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Efficiency	Level VI, CoC Tier 2	
Size / Dimension 1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	Operating Temperature	0°C ~ 60°C	
	Output Connector	USB A Receptacle	
Report errors?	Size / Dimension	1.45" L x 0.86" W x 2.00" H (36.8mm x 21.8mm x 50.8mm)	
			Report errors?

### **VEU10US050-US Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **VEU10US050-US Payment Methods**



















## **VEU10US050-US Shipping Methods**













If you have any question about VEU10US050-US, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com