

VF-S250-24A Information



For Reference Only

Part Number VF-S250-24A Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 250W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VF-S250-24A Specifications

Manufacturer Part Number VF-S250-24A Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VF-S250 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VF-S250 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Manufacturer Part Number	VF-S250-24A
Package - Series VF-S250 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Manufacturer	CUI Inc.
Package - Series VF-S250 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series VF-S250 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10.42A Power (Watts) 250W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Series	VF-S250
Voltage - Input90 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10.42APower (Watts)250WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Туре	Open Frame
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Size / Dimension 24V Voltage - Output 2 - Current - Output (Max) - Curre	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Peatures Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension - Courrent - Output (Max) - Current - Output (Max) - Courrent - Output (Ma	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 10.42A	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	10.42A
Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Power (Watts)	250W
Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, PFC, Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Efficiency	83%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)	Features	Adjustable Output, PFC, Remote On/Off, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.20" W x 1.50" H (127.0mm x 81.3mm x 38.1mm)
		Report errors?

VF-S250-24A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VF-S250-24A Payment Methods



















VF-S250-24A Shipping Methods













If you have any question about VF-S250-24A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com