

VF-S320-48A

a Quote

VF-S320-48A Information

	Part Number	VF-S320-48A	
	Manufacturer	CUI Inc.	一回感物
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
Notes	Description	AC/DC CONVERTER 48V 180W	- :S
3	Package	-	
		For the pricing/inventory/lead time, please contact	e eist
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VF-S320-48A Specifications

Manufacturer Part NumberVF-S320-48AManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)Package-Package-SeriesVF-S320TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 132 VAC, 180 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 4-Power (Watts)180W (320W Forced Air)Power (Watts)StX (3000V)Efficiency83%Operating Temperature-Poter Informeration-Mounting TypeChasis MountFotures Informeration-Size / Dimension-Over X 1.50" H (152.4mm x 101.6mm x 38.1mm)				
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesVF-S320TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 132 VAC, 180 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 43.75APower (Watts)ITE (commercial)Voltage - Isolation3xV (300V)Efficiency83%Operating Temperature-Mounting TypeChasis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	rer Part Number	VF-S320-48A		
AC DC Coverters Package - Series VF-S320 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.75A Power (Watts) 180W (320W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3KV (3000V) Efficiency 83% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chasis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	rer C	CUI Inc.		
Package-SeriesVF-S320TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 132 VAC, 180 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 43.75APower (Watts)180W (320W Forced Air)ApplicationsTE (Commercial)Voltage - Isolation3.75APoreating Temperature3.8%Operating Temperature0° ~ 70°C (With Derating)FeaturesAdjustabe Output, PFC, Universal InputMounting TypeChasis MountSize / Dimension6.00° L x 4.00° W x 1.50° H (152.4mm x 101.6mm x 38.1mm)	F	Power Supplies - External/Internal (Off-Board)		
Series VF-S320 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.75A Power (Wats) 180W (320W Forced Air) Applications ITE (commercial) Voltage - Isolation 3.8V (3000V) Efficiency 83% Operating Temperature O'C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chasis Mount Size / Dimension 6.0°' L x 4.00'' W x 1.50'' H (152.4mm x 101.6mm x 38.1mm)	A	AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 132 VAC, 180 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Current - Output (Max)3.75APower (Watts)180W (320W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3xV (3000V)Efficiency3%Operating TemperatureO'C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting Type6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	-	-		
Number of Outputs 1 Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.75A Power (Watts) 180W (320W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chasis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	V	VF-S320		
Voltage - Input 90 ~ 132 VAC, 180 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Vortage - Output 5 - Power (Watts) 180W (320W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	(Open Frame		
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.75A Power (Watts) 180W (320W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3KV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chasis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Outputs 1	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)3.75APower (Watts)180W (320W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting Type6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	nput 9	90 ~ 132 VAC, 180 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)3.75APower (Watts)180W (320W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Output 14	48V		
Voltage - Output 4-Current - Output (Max)3.75APower (Watts)180W (320W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Output 2 -	-		
Current - Output (Max) 3.75A Power (Watts) 180W (320W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	- Dutput 3	-		
Power (Watts)180W (320W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Output 4 -	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Output (Max) 3	3.75A		
Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	itts) 1	180W (320W Forced Air)		
Efficiency83%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	ns I'	ITE (Commercial)		
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	solation 3	3kV (3000V)		
FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	8	83%		
Mounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Temperature 0	0° C ~ 70°C (With Derating)		
Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	A	Adjustable Output, PFC, Universal Input		
	Гуре С	Chassis Mount		
	ension 6	5.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)		
Report		Report errors?		

VF-S320-48A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VF-S320-48A Payment MethodsImage: WIRE
transferPayPaiImage: Construction
methodsImage: Construction
methodsImage: Construction
methodsVF-S320-48A Shipping MethodsImage: Construction
methodsImage: Construction
methodsImage: Construction
methodsImage: Construction
methods

If you have any question about VF-S320-48A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com