



### **VFT150PS12 Information**



For Reference Only

Part Number VFT150PS12

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 12V 150W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **VFT150PS12 Specifications**

Manufacturer Part Number         VFT150PS12           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VFT           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         VFT           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer Part Number	VFT150PS12
Package         -           Series         VFT           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer	XP Power
Package         -           Series         VFT           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         VFT           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         8.3A           Power (Watts)         150W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Package	-
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8.3APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Series	VFT
Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8.3APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  12V  - Size / Dimension  12V  12V  12V  12V  12V  12V  12V  12	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Size / Dimension  - Current - Output (Max)  8.3A  - Current - Output (Max)  8.3A  ITE (Commercial)  3kV (3000V)  64  87%  Chassis Mount  Size / Dimension  - Chassis Mount  Size / Dimension	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Size / Dimension  Size / Dimension  Six	Voltage - Output 1	12V
Voltage - Output 4  Current - Output (Max)  8.3A  Power (Watts)  150W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Output 2	-
Current - Output (Max)  8.3A  Power (Watts)  150W  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Current - Output (Max)	8.3A
Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Power (Watts)	150W
Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Applications	ITE (Commercial)
Operating Temperature  -10°C ~ 70°C (With Derating)  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Efficiency	87%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Features	Adjustable Output, Remote Sense, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)
		Report errors?

#### **VFT150PS12 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **VFT150PS12 Payment Methods**



















## **VFT150PS12 Shipping Methods**













If you have any question about VFT150PS12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com