



VG95234J2-36-5SN Information

Heisener.com

Part Number VG95234J2-36-5SN **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 4POS WALL MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VG95234J2-36-5SN Specifications

Manufacturer Part Number VG95234J2-36-5SN Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series VG 95234, CA-B Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 36-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A		
CategoryConnectors, InterconnectsPackage-SeriesVG 95234, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Manufacturer Part Number	VG95234J2-36-5SN
Package-SeriesVG 95234, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Manufacturer	ITT Cannon, LLC
Package-SeriesVG 95234, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Category	Connectors, Interconnects
SeriesVG 95234, CA-BConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Package	-
Number of Positions4Shell Size - Insert36-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Series	VG 95234, CA-B
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated-Current Rating245A	Shell Size - Insert	36-5
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Backshell, Strain Relief - 245A	Orientation	N (Normal)
Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Backshell, Strain Relief Voltage - Rated - Current Rating 245A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 245A	Contact Finish	Silver
Current Rating 245A	Features	Backshell, Strain Relief
	Voltage - Rated	-
Report errors?	Current Rating	245A
		Report errors?

VG95234J2-36-5SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VG95234J2-36-5SN Payment Methods



















VG95234J2-36-5SN Shipping Methods













If you have any question about VG95234J2-36-5SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com