



VHK50W-Q24-S3R3 Information



For Reference Only

Part Number VHK50W-Q24-S3R3

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description CONVERTER DC-DC 3.3V 10A 33W

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VHK50W-Q24-S3R3 Specifications

| Manufacturer Part Number VHK50W-Q24-S3R3 Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series VHK50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | | | |
|--|--------------------------|--|----------------|
| Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series VHK50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Manufacturer Part Number | VHK50W-Q24-S3R3 | |
| Package Module Series VHK50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Manufacturer | CUI Inc. | |
| Package Module Series VHK50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Category | Power Supplies - External/Internal (Off-Board) | |
| Series VHK50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | | DC DC Converters | |
| Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Package | Module | |
| Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Series | VHK50W | |
| Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Туре | Isolated | |
| Number of Outputs 1 Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Voltage - Input (Min) | 9V | |
| Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Voltage - Input (Max) | 36V | |
| Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Number of Outputs | 1 | |
| Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Voltage - Output 1 | 3.3V | |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) 10A - Output (Max) 50W Chassis Mount - Company output (Max) - Outp | Voltage - Output 2 | - | |
| Current - Output (Max) Power (Watts) Applications Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 10A 50W Chassis Mount 10A 10A 10A 10A 10A 10A 10A 10 | Voltage - Output 3 | - | |
| Power (Watts) 50W Applications - Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Voltage - Output 4 | - | |
| Applications Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension -40°C ~ 85°C 75% Konstant (107.5mm x 101.8mm x 38.0mm) | Current - Output (Max) | 10A | |
| Operating Temperature -40°C ~ 85°C Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Power (Watts) | 50W | |
| Efficiency 75% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Applications | - | |
| Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Operating Temperature | -40°C ~ 85°C | |
| Package / Case Module Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Efficiency | 75% | |
| Size / Dimension 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | Mounting Type | Chassis Mount | |
| · | Package / Case | Module | |
| Demonstration of the second control of the s | Size / Dimension | 4.23" L x 4.01" W x 1.50" H (107.5mm x 101.8mm x 38.0mm) | |
| Report errors | | | Report errors? |

VHK50W-Q24-S3R3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VHK50W-Q24-S3R3 Payment Methods



















VHK50W-Q24-S3R3 Shipping Methods













If you have any question about VHK50W-Q24-S3R3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com