

VI-21Z-CX-S Information



For Reference Only

Part Number VI-21Z-CX-S
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 2V 30W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-21Z-CX-S Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series V1-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Manufacturer Part Number	VI-21Z-CX-S
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Manufacturer	Vicor Corporation
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Category	Power Supplies - Board Mount
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Series	VI-200
Voltage - Input (Min) 21V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Туре	Isolated Module
Voltage - Input (Max) 32V Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Number of Outputs	1
Voltage - Output 1 2V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Voltage - Input (Min)	21V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 30W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Voltage - Input (Max)	32V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Voltage - Output 1	2V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C Efficiency 90%	Voltage - Output 2	-
Current - Output (Max) $30A$ Power (Watts) $30W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Output 3	
Power (Watts) $30W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Current - Output (Max)	30A
ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency90%	Power (Watts)	30W
Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Isolation	3kV (3000V)
Operating Temperature -25°C ~ 85°C Efficiency 90%	Applications	ITE (Commercial)
Efficiency 90%	Features	OCP, OTP, OVP, SCP
	Operating Temperature	-25°C ~ 85°C
	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)	Size / Dimension	4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-21Z-CX-S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-21Z-CX-S Payment Methods



















VI-21Z-CX-S Shipping Methods













If you have any question about VI-21Z-CX-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com