

# VI-24X-MY-F4

a Quote

#### VI-24X-MY-F4 Information

| The second second  | Part Number  | VI-24X-MY-F4  |         |
|--------------------|--------------|---|---------|
|                    | Manufacturer | Vicor Corporation   |         |
|                    | Category     | Power Supplies - Board Mount<br>DC DC Converters                    | - 78E   |
|                    | Description  | CONVERTER MOD DC/DC 5.2V 50W  | - AR 15 |
|                    | Package      | Full Brick  |         |
|                    |              | For the pricing/inventory/lead time, please contact                 |         |
|                    |              | us  |         |
| For Reference Only |              | Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com | Request |

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## VI-24X-MY-F4 Specifications

| Manufacturer Part Number | VI-24X-MY-F4  |  |  |
|--------------------------|---|--|--|
| Manufacturer             | Vicor Corporation                                       |  |  |
| Category                 | Power Supplies - Board Mount                            |  |  |
|                          | DC DC Converters  |  |  |
| Package                  | Full Brick  |  |  |
| Series                   | VI-200  |  |  |
| Туре                     | Isolated Module   |  |  |
| Number of Outputs        | 1   |  |  |
| Voltage - Input (Min)    | 55V   |  |  |
| Voltage - Input (Max)    | 100V  |  |  |
| Voltage - Output 1       | 5.2V  |  |  |
| Voltage - Output 2       | -   |  |  |
| Voltage - Output 3       | _   |  |  |
| Voltage - Output 4       | _   |  |  |
| Current - Output (Max)   | 9.62A   |  |  |
| Power (Watts)            | 50W   |  |  |
| Voltage - Isolation      | 3kV (3000V)   |  |  |
| Applications             | ITE (Commercial)  |  |  |
| Features                 | OCP, OTP, OVP, SCP                                      |  |  |
| Operating Temperature    | -55°C ~ 85°C  |  |  |
| Efficiency               | 90%   |  |  |
| Mounting Type            | Through Hole  |  |  |
| Package / Case           | Full Brick  |  |  |
| Size / Dimension         | 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm) |  |  |
|                          |   |  |  |

| Supplier Device Package | - |                |
|-------------------------|---|----------------|
| Control Features        | - |                |
|                         |   | Report errors? |

### VI-24X-MY-F4 Guarantees



If you have any question about VI-24X-MY-F4, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com