

VI-2NL-EX-F4 Information



For Reference Only

Part Number VI-2NL-EX-F4
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 28V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-2NL-EX-F4 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Category Power Supplies - Boad DC DC Converters Package Full Brick Vi-200 Type Isolated Module Number of Outputs Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 -	rd Mount
Category Power Supplies - Boar DC DC Converters Package Full Brick VI-200 Type Isolated Module Number of Outputs Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2	rd Mount
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Output 1 28V Voltage - Output 2	rd Mount
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 76V Voltage - Output 1 28V Voltage - Output 2	
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 76V Voltage - Output 1 28V Voltage - Output 2 -	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 36V Voltage - Input (Max) 76V Voltage - Output 1 28V Voltage - Output 2 -	
Number of Outputs Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 -	
Voltage - Input (Min) 36V Voltage - Input (Max) 76V Voltage - Output 1 28V Voltage - Output 2 -	
Voltage - Input (Max) 76V Voltage - Output 1 28V Voltage - Output 2 -	
Voltage - Output 1 28V Voltage - Output 2 -	
Voltage - Output 2	
Voltage - Output 3	
Voltage - Output 4	
Current - Output (Max) 2.68A	
Power (Watts) 75W	
Voltage - Isolation 3kV (3000V)	
Applications ITE (Commercial)	
Features OCP, OTP, OVP, SCI	
Operating Temperature $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 88%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 1	
	.05" H (116.8mm x 47.2mm x 26.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-2NL-EX-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-2NL-EX-F4 Payment Methods





















VI-2NL-EX-F4 Shipping Methods













If you have any question about VI-2NL-EX-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com