

### **VI-2TF-MV-S Information**



For Reference Only

Part Number VI-2TF-MV-S
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 72V 150W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VI-2TF-MV-S Specifications**

Manufacturer Part Number         VI-2TF-MV-S           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         72V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.08A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -55°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         72V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.08A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -55°C ~ 85°C           Efficiency         90%	Manufacturer Part Number	
DC DC Converters	Manufacturer	Vicor Corporation
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         72V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.08A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -55°C ~ 85°C           Efficiency         90%	Category	Power Supplies - Board Mount
Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Output 1         72V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.08A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -55°C ~ 85°C           Efficiency         90%		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         66V           Voltage - Input (Max)         160V           Voltage - Output 1         72V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         2.08A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -55°C ~ 85°C           Efficiency         90%	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       66V         Voltage - Input (Max)       160V         Voltage - Output 1       72V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.08A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -55°C ~ 85°C         Efficiency       90%	Series	VI-200
Voltage - Input (Min)       66V         Voltage - Input (Max)       160V         Voltage - Output 1       72V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.08A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -55°C ~ 85°C         Efficiency       90%	Туре	Isolated Module
Voltage - Input (Max)       160V         Voltage - Output 1       72V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.08A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -55°C ~ 85°C         Efficiency       90%	Number of Outputs	1
Voltage - Output 1       72V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.08A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -55°C ~ 85°C         Efficiency       90%	Voltage - Input (Min)	66V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       2.08A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -55°C ~ 85°C         Efficiency       90%	Voltage - Input (Max)	160V
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -55°C ~ 85°C  Efficiency  90%	Voltage - Output 1	72V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -55°C ~ 85°C  Efficiency  90%	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  150W  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -55°C ~ 85°C  Efficiency  90%	Voltage - Output 3	
Power (Watts) $150W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-55^{\circ}$ C ~ $85^{\circ}$ CEfficiency90%	Voltage - Output 4	-
Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -55°C ~ 85°C  Efficiency 90%	Current - Output (Max)	2.08A
Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -55°C ~ 85°C  Efficiency 90%	Power (Watts)	150W
Features OCP, OTP, OVP, SCP Operating Temperature -55°C ~ 85°C Efficiency 90%	Voltage - Isolation	3kV (3000V)
Operating Temperature -55°C ~ 85°C Efficiency 90%	Applications	ITE (Commercial)
Efficiency 90%	Features	OCP, OTP, OVP, SCP
·	Operating Temperature	-55°C ~ 85°C
Mounting Type Through Hole	Efficiency	90%
	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)	Size / Dimension	4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VI-2TF-MV-S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## VI-2TF-MV-S Payment Methods



















## **VI-2TF-MV-S Shipping Methods**













If you have any question about VI-2TF-MV-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com