

### VI-2W0-CX-S Information



For Reference Only

Part Number VI-2W0-CX-S
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 5V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# VI-2W0-CX-S Specifications

Manufacturer Part Number         VI-2W0-CX-S           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%           Mounting Type         Through Hole		
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Manufacturer Part Number	
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Manufacturer	Vicor Corporation
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Category	Power Supplies - Board Mount
Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%		DC DC Converters
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Package	Full Brick
Number of Outputs       1         Voltage - Input (Min)       18V         Voltage - Input (Max)       36V         Voltage - Output 1       5V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       15A         Power (Watts)       75W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -25°C ~ 85°C         Efficiency       90%	Series	VI-200
Voltage - Input (Min)       18V         Voltage - Input (Max)       36V         Voltage - Output 1       5V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       15A         Power (Watts)       75W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -25°C ~ 85°C         Efficiency       90%	Туре	Isolated Module
Voltage - Input (Max)         36V           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Number of Outputs	1
Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         15A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C           Efficiency         90%	Voltage - Input (Min)	18V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       15A         Power (Watts)       75W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP         Operating Temperature       -25°C ~ 85°C         Efficiency       90%	Voltage - Input (Max)	36V
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -25°C ~ 85°C  Efficiency  90%	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -25°C ~ 85°C  Efficiency  90%	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  75W  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature  -25°C ~ 85°C  Efficiency  90%	Voltage - Output 3	
Power (Watts) 75W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency $90\%$	Current - Output (Max)	15A
Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP  Operating Temperature -25°C ~ 85°C  Efficiency 90%	Power (Watts)	75W
Features OCP, OTP, OVP, SCP Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Efficiency 90%	Voltage - Isolation	3kV (3000V)
Operating Temperature -25°C ~ 85°C Efficiency 90%	Applications	ITE (Commercial)
Efficiency 90%	Features	OCP, OTP, OVP, SCP
·	Operating Temperature	-25°C ~ 85°C
Mounting Type Through Hole	Efficiency	90%
	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)	Size / Dimension	4.60" L x 1.80" W x 0.52" H (116.8mm x 45.7mm x 13.2mm)

Supplier Device Package	-
Control Features	-
	Report errors?

### VI-2W0-CX-S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# VI-2W0-CX-S Payment Methods



















## VI-2W0-CX-S Shipping Methods













If you have any question about VI-2W0-CX-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com