

VI-2W3-IX-F3 Information



For Reference Only

Part Number VI-2W3-IX-F3
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 24V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-2W3-IX-F3 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature		
Power Supplies - Board Mount		
DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Vico	orporation
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Powe	upplies - Board Mount
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	DC I	Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Full	k
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	VI-2	
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Isola	Module
Voltage - Input (Max) 36V Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	1	
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	18V	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	36V	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3.13A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	24V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	
Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	3.13.	
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	75W	
Features OCP, OTP, OVP, SCP	3kV	00V)
	ITE	mmercial)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	OCP	ΓP, OVP, SCP
	-40°C	85°C
Efficiency 90%	90%	
Mounting Type Through Hole	Thro	Hole
Package / Case Full Brick	Full	:k
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	4.60'	x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-2W3-IX-F3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-2W3-IX-F3 Payment Methods





















VI-2W3-IX-F3 Shipping Methods













If you have any question about VI-2W3-IX-F3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com