



# VI-B2X-CX-F4 Information

Heisener.com

Part Number VI-B2X-CX-F4 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 5.2V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## VI-B2X-CX-F4 Specifications

Manufacturer Part Number  Manufacturer  Vicor Corporation  Category  Power Supplies - I  DC DC Converter  Package  Full Brick  VI-200  Type  Isolated Module  Number of Outputs  Voltage - Input (Min)  Voltage - Input (Max)  Voltage - Output 1  Voltage - Output 2  Voltage - Output 3	Board Mount
Category  Power Supplies - I  DC DC Converter  Package  Full Brick  VI-200  Type  Isolated Module  Number of Outputs  Voltage - Input (Min)  Voltage - Input (Max)  Voltage - Output 1  Voltage - Output 2  -	Board Mount
Package Full Brick Series VI-200  Type Isolated Module Number of Outputs 1  Voltage - Input (Min) 21V  Voltage - Input (Max) 56V  Voltage - Output 1 5.2V  Voltage - Output 2 -	
Package Full Brick VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 -	'S
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 21V Voltage - Input (Max) 56V Voltage - Output 1 5.2V Voltage - Output 2 -	
Type Isolated Module  Number of Outputs 1  Voltage - Input (Min) 21V  Voltage - Input (Max) 56V  Voltage - Output 1 5.2V  Voltage - Output 2 -	
Number of Outputs  Voltage - Input (Min)  Voltage - Input (Max)  Voltage - Output 1  Voltage - Output 2  -	
Voltage - Input (Min)  Voltage - Input (Max)  Voltage - Output 1  Voltage - Output 2  -	
Voltage - Input (Max) 56V  Voltage - Output 1 5.2V  Voltage - Output 2 -	
Voltage - Output 1 5.2V Voltage - Output 2 -	
Voltage - Output 2 -	
Voltage - Output 3	
Voltage - Output 4	
Current - Output (Max) 14.42A	
Power (Watts) 75W	
Voltage - Isolation 3kV (3000V)	
Applications ITE (Commercial)	)
Features OCP, OTP, OVP,	SCP
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W	
	x 1.05" H (116.8mm x 47.2mm x 26.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### VI-B2X-CX-F4 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VI-B2X-CX-F4 Payment Methods

































If you have any question about VI-B2X-CX-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com