

VI-B32-IX-B1 Information

Heisener.com

Part Number VI-B32-IX-B1
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 15V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-B32-IX-B1 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Factories Vi-B32-IX-B1 Violage - Output 1 ISV Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) TSW Voltage - Isolation Applications Features OCP, OTP, OVP, SCP Operating Temperature Power (Watts) OOV		
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Manufacturer Part Number	VI-B32-IX-B1
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Category	Power Supplies - Board Mount
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Series	VI-200
Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Туре	Isolated Module
Voltage - Input (Max) 60V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Number of Outputs	1
Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Voltage - Input (Min)	42V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Voltage - Input (Max)	60V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Voltage - Output 2	-
Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -40°C ~ 85°C	Voltage - Output 3	-
Power (Watts) $75W$ Voltage - Isolation $3kV$ (3000V)ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesOCP, OTP, OVP, SCPOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output (Max)	5A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Power (Watts)	75W
Features OCP, OTP, OVP, SCP Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Isolation	3kV (3000V)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	OCP, OTP, OVP, SCP
Definion or	Operating Temperature	-40°C ~ 85°C
Efficiency 90%	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)	Size / Dimension	4.60" L x 2.40" W x 1.07" H (116.8mm x 61.0mm x 27.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-B32-IX-B1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-B32-IX-B1 Payment Methods





















VI-B32-IX-B1 Shipping Methods













If you have any question about VI-B32-IX-B1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com