

VI-B3D-CX-F2 Information

Heisener.com

Part Number VI-B3D-CX-F2 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 85V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-B3D-CX-F2 Specifications

Manufacturer Part Number VI-B3D-CX-F2 Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 85°C		
Power Supplies - Board Mount	Manufacturer Part Number	VI-B3D-CX-F2
DC DC Converters	Manufacturer	Vicor Corporation
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Category	Power Supplies - Board Mount
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Series	VI-200
Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Туре	Isolated Module
Voltage - Input (Max) 60V Voltage - Output 1 85V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features 85V	Voltage - Input (Min)	42V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Input (Max)	60V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Output 1	85V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Output 2	-
Current - Output (Max) 882mA Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Output 3	-
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Voltage - Output 4	-
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Current - Output (Max)	882mA
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Power (Watts)	75W
Features OCP, OTP, OVP, SCP	Voltage - Isolation	3kV (3000V)
	Applications	ITE (Commercial)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	OCP, OTP, OVP, SCP
	Operating Temperature	-25°C ~ 85°C
Efficiency 90%	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	Size / Dimension	4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-B3D-CX-F2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-B3D-CX-F2 Payment Methods



















VI-B3D-CX-F2 Shipping Methods













If you have any question about VI-B3D-CX-F2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com