



VI-B3M-CX-F1 Information

Heisener.com

Part Number VI-B3M-CX-F1 **Manufacturer** Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 10V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-B3M-CX-F1 Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP		
Power Supplies - Board Mount		VI-B3M-CX-F1
DC DC Converters		
Package Full Brick Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Po	Power Supplies - Board Mount
Series VI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	D	DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Fu	Full Brick
Number of Outputs 1 Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	V	VI-200
Voltage - Input (Min) 42V Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	Is	Isolated Module
Voltage - Input (Max) 60V Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	1	1
Voltage - Output 1 10V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	in) 42	42V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	ax) 60	60V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	10	10V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	-
Current - Output (Max) 7.5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	-
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	-	-
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	1 (ax) 7.	7.5A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	75	75W
Features OCP, OTP, OVP, SCP	31	3kV (3000V)
	ΓI	ITE (Commercial)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	O	OCP, OTP, OVP, SCP
Operating Temperature 25 C 05 C	ture -2	-25°C ~ 85°C
Efficiency 90%	90	90%
Mounting Type Through Hole	Ti	Through Hole
Package / Case Full Brick	Fu	Full Brick
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	4.	4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)

Supplier Device Package	-
Control Features	-
	Report errors?

VI-B3M-CX-F1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-B3M-CX-F1 Payment Methods



















VI-B3M-CX-F1 Shipping Methods













If you have any question about VI-B3M-CX-F1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com