



## **VI-BNV-MW-F4 Information**

Heisener.com

Part Number VI-BNV-MW-F4 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 5.8V 100W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## VI-BNV-MW-F4 Specifications

Manufacturer Part Number  Manufacturer  Category  Power Supplies - Board Mount  DC DC Converters  Package  Full Brick  Series  VI-200  Type  Isolated Module  Number of Outputs  1  Voltage - Input (Min)  Voltage - Input (Max)  Voltage - Output 1  Voltage - Output 2  Voltage - Output 3  -  Voltage - Output 4  Current - Output (Max)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP  Operating Temperature	
Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         36V           Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
DC DC Converters	
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         36V           Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         36V           Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         36V           Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Number of Outputs       1         Voltage - Input (Min)       36V         Voltage - Input (Max)       76V         Voltage - Output 1       5.8V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       17.24A         Power (Watts)       100W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	
Voltage - Input (Min)         36V           Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Input (Max)         76V           Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 1         5.8V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       17.24A         Power (Watts)       100W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	
Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         17.24A           Power (Watts)         100W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	
Current - Output (Max) 17.24A  Power (Watts) 100W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	
Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	
Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Features OCP, OTP, OVP, SCP	
Operating Temperature -55°C ~ 85°C	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VI-BNV-MW-F4 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VI-BNV-MW-F4 Payment Methods



















# VI-BNV-MW-F4 Shipping Methods













If you have any question about VI-BNV-MW-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com