

VI-LC61-EV Information

Heisener.com

For Reference Only

Category

Part Number VI-LC61-EV

Manufacturer Vicor Corporation

Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description

DC-DC SWITCHER: COMPAC SERIES

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VI-LC61-EV Specifications

Manufacturer Part Number VI-LC61-EV Manufacturer Vicor Corporation Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series ComPAC? Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series ComPAC? Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Manufacturer Part Number	VI-LC61-EV
Package - Series ComPAC? Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Manufacturer	Vicor Corporation
Package - Series ComPAC? Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 15.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ComPAC? Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Package	-
Voltage - Input (Min) 200V Voltage - Input (Max) 400V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Series	ComPAC?
Voltage - Input (Max) 400 V Number of Outputs 1 Voltage - Output 1 12 V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5 A Power (Watts) 150 W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Туре	Isolated
Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Voltage - Input (Min)	200V
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Voltage - Input (Max)	400V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.5A Power (Watts) 150W Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Size / Dimension - - - - - - - - - - - - -	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) 12.5A Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Size / Dimension 12.5A 150W Commercial -10°C ~ 85°C Chassis Mount -10°C ~ 85°C	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Size / Dimension 150W 150W 150W 150W 150W 150W 150W 160W 170C ~ 85°C 160W 170C ~ 85°C 170C ~	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Current - Output (Max)	12.5A
Operating Temperature -10°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Power (Watts)	150W
Efficiency 88% Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Applications	ITE (Commercial)
Mounting Type Chassis Mount Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Operating Temperature	-10°C ~ 85°C
Package / Case - Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Efficiency	88%
Size / Dimension 8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)	Mounting Type	Chassis Mount
	Package / Case	-
Report errors?	Size / Dimension	8.63" L x 2.50" W x 0.99" H (219.2mm x 64.5mm x 25.2mm)
		Report errors?

VI-LC61-EV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VI-LC61-EV Payment Methods



















VI-LC61-EV Shipping Methods













If you have any question about VI-LC61-EV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com