



#### VJ0402A330JNAAJ00 Information

w

For Reference Only

Part Number VJ0402A330JNAAJ00 Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 33PF 50V NP0 0402

**Package** 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## VJ0402A330JNAAJ00 Specifications

Manufacturer Part Number         VJ0402A330JNAAJ00           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         0402 (1005 Metric)           Series         VJ           Capacitance         33pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC, Epoxy           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Spacing         -		
Category         Capacitors           Package         0402 (1005 Metric)           Series         VJ           Capacitance         33pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC, Epoxy           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -	Manufacturer Part Number	VJ0402A330JNAAJ00
Package         0402 (1005 Metric)           Series         VJ           Capacitance         33pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC, Epoxy           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -	Manufacturer	Vishay Vitramon
Package         0402 (1005 Metric)           Series         VJ           Capacitance         33pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC, Epoxy           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -	Category	Capacitors
Series         VJ           Capacitance         33pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Non-Magnetic           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC, Epoxy           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -		Ceramic Capacitors
Capacitance 33pF Tolerance ±5%  Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Non-Magnetic Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC, Epoxy Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Package	0402 (1005 Metric)
Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Non-Magnetic  Ratings - Case General Purpose  Failure Rate - Surface Mount, MLCC, Epoxy  Package / Case 0402 (1005 Metric)  Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max) - O.024" (0.60mm)  Lead Spacing - Commondance of the state of th	Series	VJ
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesNon-MagneticRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCC, EpoxyPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.024" (0.60mm)Lead Spacing-	Capacitance	33pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  Non-Magnetic  Ratings  - Applications  General Purpose  Failure Rate  Mounting Type  Surface Mount, MLCC, Epoxy  Package / Case  0402 (1005 Metric)  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  COG, NP0  CO	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesNon-MagneticRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCC, EpoxyPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.024" (0.60mm)Lead Spacing-	Voltage - Rated	50V
FeaturesNon-MagneticRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCC, EpoxyPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.024" (0.60mm)Lead Spacing-	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC, Epoxy Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC, Epoxy Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Features	Non-Magnetic
Failure Rate - Mounting Type Surface Mount, MLCC, Epoxy Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC, Epoxy Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Applications	General Purpose
Package / Case       0402 (1005 Metric)         Size / Dimension       0.039" L x 0.020" W (1.00mm x 0.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.024" (0.60mm)         Lead Spacing       -	Failure Rate	-
Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -	Mounting Type	Surface Mount, MLCC, Epoxy
Height - Seated (Max)  Thickness (Max)  Lead Spacing  -  0.024" (0.60mm)  -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.024" (0.60mm) Lead Spacing -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.024" (0.60mm)
Lead Style -	Lead Spacing	-
2000 50,10	Lead Style	-
Report errors?		Report errors?

#### VJ0402A330JNAAJ00 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### VJ0402A330JNAAJ00 Payment Methods





















## VJ0402A330JNAAJ00 Shipping Methods













If you have any question about VJ0402A330JNAAJ00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com