

VJ0402D0R7BLXAC

VJ0402D0R7BLXAC Information



For Reference Only

Part Number VJ0402D0R7BLXAC Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.7PF 25V C0G/NP0 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0402D0R7BLXAC Specifications

Manufacturer Part Number VJ0402D0R7BLXAC Manufacturer Vishay Vitramon Category Capacitors Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 0.7pF Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)		
Category Capacitors Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 0.7pF Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Manufacturer Part Number	VJ0402D0R7BLXAC
Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 0.7pF Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Manufacturer	Vishay Vitramon
Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 0.7pF Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Category	Capacitors
Series VJ HIFREQ Capacitance 0.7pF Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)		Ceramic Capacitors
Capacitance0.7pFTolerance±0.1pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)	Package	0402 (1005 Metric)
Tolerance ±0.1pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Series	VJ HIFREQ
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)	Capacitance	0.7pF
Temperature Coefficient $C0G$, NP0Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension 0.040° L x 0.020° W (1.02 mm x 0.51 mm)Height - Seated (Max)-Thickness (Max) 0.024° (0.61 mm)	Tolerance	±0.1pF
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)	Voltage - Rated	25V
Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Applications	RF, Microwave, High Frequency
Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Failure Rate	-
Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) - 0.024" (0.61mm)	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.024" (0.61mm)	Size / Dimension	0.040" L x 0.020" W (1.02mm x 0.51mm)
	Height - Seated (Max)	-
Lead Spacing	Thickness (Max)	0.024" (0.61mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

VJ0402D0R7BLXAC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0402D0R7BLXAC Payment Methods



















VJ0402D0R7BLXAC Shipping Methods













If you have any question about VJ0402D0R7BLXAC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com