



### VJ0402D2R4DLAAJ Information



For Reference Only

Part Number VJ0402D2R4DLAAJ
Manufacturer Vishay Vitramon
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 2.4PF 50V C0G/NP0 0402

**Package** 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# VJ0402D2R4DLAAJ Specifications

Manufacturer Part Number         VJ0402D2R4DLAAJ           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         0402 (1005 Metric)           Series         VJ HIFREQ           Capacitance         2.4pF           Tolerance         ±0.5pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         0.024" (0.61mm)           Lead Spacing         -           Lead Spacing         -		
Category         Capacitors           Package         0402 (1005 Metric)           Series         VJ HIFREQ           Capacitance         2.4pF           Tolerance         ±0.5pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.61mm)           Lead Spacing         -	Manufacturer Part Number	VJ0402D2R4DLAAJ
Package         0402 (1005 Metric)           Series         VJ HIFREQ           Capacitance         2.4pF           Tolerance         ±0.5pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.61mm)           Lead Spacing         -	Manufacturer	Vishay Vitramon
Package         0402 (1005 Metric)           Series         VJ HIFREQ           Capacitance         2.4pF           Tolerance         ±0.5pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.61mm)           Lead Spacing         -	Category	Capacitors
Series         VJ HIFREQ           Capacitance         2.4pF           Tolerance         ±0.5pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.61mm)           Lead Spacing         -		Ceramic Capacitors
Capacitance2.4pFTolerance±0.5pFVoltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing-	Package	0402 (1005 Metric)
Tolerance ±0.5pF  Voltage - Rated 50V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features High Q, Low Loss  Ratings - Applications RF, Microwave, High Frequency  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm)  Height - Seated (Max) -  Thickness (Max) 0.024" (0.61mm)  Lead Spacing -	Series	VJ HIFREQ
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing-	Capacitance	2.4pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing-	Tolerance	±0.5pF
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing-	Voltage - Rated	50V
Features High Q, Low Loss  Ratings - RF, Microwave, High Frequency  Failure Rate - Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm)  Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)  Lead Spacing	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm)  Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm)  Lead Spacing -	Applications	RF, Microwave, High Frequency
Package / Case       0402 (1005 Metric)         Size / Dimension       0.040" L x 0.020" W (1.02mm x 0.51mm)         Height - Seated (Max)       -         Thickness (Max)       0.024" (0.61mm)         Lead Spacing       -	Failure Rate	-
Size / Dimension       0.040" L x 0.020" W (1.02mm x 0.51mm)         Height - Seated (Max)       -         Thickness (Max)       0.024" (0.61mm)         Lead Spacing       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  -  0.024" (0.61mm)  -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.024" (0.61mm)  Lead Spacing -	Size / Dimension	0.040" L x 0.020" W (1.02mm x 0.51mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.024" (0.61mm)
Lead Style -	Lead Spacing	-
Zona style	Lead Style	-
Report errors?		Report errors?

#### VJ0402D2R4DLAAJ Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VJ0402D2R4DLAAJ Payment Methods



















## VJ0402D2R4DLAAJ Shipping Methods













If you have any question about VJ0402D2R4DLAAJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com