



VJ0402D3R6DLCAJ Information



For Reference Only

Part Number VJ0402D3R6DLCAJ
Manufacturer Vishay Vitramon
Category Capacitors

Ceramic Capacitors

Description CAP CER 3.6PF 200V C0G/NP0 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0402D3R6DLCAJ Specifications

| Manufacturer Part Number VJ0402D3R6DLCAJ Manufacturer Vishay Vitramon Category Capacitors Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 3.6pF Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Style - | | |
|--|--------------------------|---------------------------------------|
| Category Capacitors Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 3.6pF Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Manufacturer Part Number | VJ0402D3R6DLCAJ |
| Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 3.6pF Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Manufacturer | Vishay Vitramon |
| Package 0402 (1005 Metric) Series VJ HIFREQ Capacitance 3.6pF Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Category | Capacitors |
| Series VJ HIFREQ Capacitance 3.6pF Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | | Ceramic Capacitors |
| Capacitance3.6pFTolerance±0.5pFVoltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing- | Package | 0402 (1005 Metric) |
| Tolerance ±0.5pF Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Series | VJ HIFREQ |
| Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Capacitance | 3.6pF |
| Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - COG, NP0 - COG, NP0 | Tolerance | ±0.5pF |
| Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing- | Voltage - Rated | 200V |
| FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.61mm)Lead Spacing- | Temperature Coefficient | C0G, NP0 |
| Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Operating Temperature | -55°C ~ 125°C |
| Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Features | High Q, Low Loss |
| Failure Rate - Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Applications | RF, Microwave, High Frequency |
| Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Failure Rate | - |
| Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Mounting Type | Surface Mount, MLCC |
| Height - Seated (Max) Thickness (Max) Lead Spacing - 0.024" (0.61mm) - | Package / Case | 0402 (1005 Metric) |
| Thickness (Max) 0.024" (0.61mm) Lead Spacing - | Size / Dimension | 0.040" L x 0.020" W (1.02mm x 0.51mm) |
| Lead Spacing - | Height - Seated (Max) | - |
| | Thickness (Max) | 0.024" (0.61mm) |
| Lead Style - | Lead Spacing | - |
| • | Lead Style | - |
| Report errors? | | Report errors? |

VJ0402D3R6DLCAJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0402D3R6DLCAJ Payment Methods

































If you have any question about VJ0402D3R6DLCAJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com