

## VJ0603D360FLXAP

### VJ0603D360FLXAP Information



For Reference Only

Part Number VJ0603D360FLXAP
Manufacturer Vishay Vitramon
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 36PF 25V C0G/NP0 0603

**Package** 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **VJ0603D360FLXAP Specifications**

Manufacturer Part Number         VJ0603D360FLXAP           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         0603 (1608 Metric)           Series         VJ HIFREQ           Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0603 (1608 Metric)           Series         VJ HIFREQ           Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	VJ0603D360FLXAP
Package         0603 (1608 Metric)           Series         VJ HIFREQ           Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay Vitramon
Package         0603 (1608 Metric)           Series         VJ HIFREQ           Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         VJ HIFREQ           Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         36pF           Tolerance         ±1%           Voltage - Rated         25V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -	Package	0603 (1608 Metric)
Tolerance         ±1%           Voltage - Rated         25 V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)           Lead Spacing         -           Lead Style         -	Series	VJ HIFREQ
Voltage - Rated  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  High Q, Low Loss  Ratings  - Applications  RF, Microwave, High Frequency  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0603 (1608 Metric)  Size / Dimension  0.063" L x 0.031" W (1.60mm x 0.80mm)  Height - Seated (Max)  - Thickness (Max)  0.037" (0.94mm)  Lead Spacing  - Lead Style	Capacitance	36pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  High Q, Low Loss  Ratings  -  Applications  RF, Microwave, High Frequency  Failure Rate  -  Mounting Type  Surface Mount, MLCC  Package / Case  0603 (1608 Metric)  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  COG, NPO  COG, NPO  -55°C ~ 125°C  High Q, Low Loss  Arrive Low Loss  High Q, Low Loss  Alternative Low Loss  High Q, Low Loss  High Q, Low Loss  And Low Loss  High Q, Low Loss  And Low Loss  Applications  -  10 00300000000000000000000000000000000	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
Features High Q, Low Loss  Ratings - Applications RF, Microwave, High Frequency  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)  Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm)  Lead Spacing - Lead Style -	Temperature Coefficient	COG, NPO
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       0603 (1608 Metric)         Size / Dimension       0.063" L x 0.031" W (1.60mm x 0.80mm)         Height - Seated (Max)       -         Thickness (Max)       0.037" (0.94mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.063" L x 0.031" W (1.60mm x 0.80mm)         Height - Seated (Max)       -         Thickness (Max)       0.037" (0.94mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.037" (0.94mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.037" (0.94mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### VJ0603D360FLXAP Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VJ0603D360FLXAP Payment Methods



















### VJ0603D360FLXAP Shipping Methods













If you have any question about VJ0603D360FLXAP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com