

VJ0805D120KLAAP

VJ0805D120KLAAP Information

Contract service contraction	Part Number Manufacturer Category Description Package	VJ0805D120KLAAP Vishay Vitramon Capacitors Ceramic Capacitors CAP CER 12PF 50V C0G/NP0 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VJ0805D120KLAAP Specifications

Manufacturer Part Number VJ080SD120KLAAP Manufacturer Vishay Vitramon Category Capacitors Ceramic Capacitors Ceramic Capacitors Package 0805 (2012 Metric) Series VI HIFREQ Capacitance 12pF Tolerance ±10% Voltage - Rated 50% Concord Operating Temperature 050, P00 Pactangs 050, P00 Pactangs 05% Concord Applications 55% Concord Patienter Score Market Score Algore Applications RF, Microwave, High Frequency Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Height - Seated (Max) - Lead Spacing - Lead Spacing - Lead Spacing -		
CategoryCapacitorsPackage0805 (2012 Metric)SeriesVJ HIFREQCapacitance12pFTolerance±10%Voltage - RatedSoVTomperature CoefficientCoG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsSoVMounting TypeSufface Mount, MLCCPackage / Case0007°L x 0.049° W (2.00mm x 1.25mm)Fieldy - Seated (Max).Hight - Seated (Max).Hickness (Max)0.057° (1.45mm)Lead Spacing.Lead Style.	Manufacturer Part Number	VJ0805D120KLAAP
Ceranic CapacitorsPackage0805 (2012 Metric)SeriesVJ HIFREQCapacitance12pFTolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsSurface Mount, MLCCMounting Type0805 (2012 Metric)Size / Dimension0.057" (1.45mm)High Spacing-Thickness (Max)0.057" (1.45mm)Lead Style-Lead Style-	Manufacturer	Vishay Vitramon
Package0805 (2012 Metric)SeriesVJ HIFREQCapacitance12pFTolerance±10%Voltage Rated50VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Nourting TypeSurface Mount, MLCCSize / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Category	Capacitors
SeriesVJ HIFREQCapacitance12pFTolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)High P. Seated (Max)-Thickness (Max)0.55° (1.45mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance 12pF Tolerance ±10% Yoltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension -0079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing0.057" (1.45mm)Lead Style-	Series	VJ HIFREQ
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Size / Dimension-Hight - Seated (Max)-Hight Seated (Max)-Lead Spacing0.057" (1.45mm)Lead Style-State Style-	Capacitance	12pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-Strace Mount (Max)-Strace Mount (Max)- <td>Tolerance</td> <td>±10%</td>	Tolerance	±10%
Operating Temperature.55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.057" (1.45mm)Lead Spacing-Lead Style-State Style-<	Voltage - Rated	50V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Height Seated (Max)-Starter Max-Starter Max-St	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Features	High Q, Low Loss
Failure Rate-Foilure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.057" (1.45mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ0805D120KLAAP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D120KLAAP Payment Methods





If you have any question about VJ0805D120KLAAP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com