



VJ0805D241JLXAR Information

Heisener.com

VJ0805D241JLXAR Part Number Manufacturer Vishay Vitramon

Category Capacitors

Description CAP CER 240PF 25V NP0 0805

Ceramic Capacitors

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0805D241JLXAR Specifications

Manufacturer Part Number VJ0805D241JLXAR Manufacturer Vishay Vitramon Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Manufacturer Part Number	VJ0805D241JLXAR
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Category	Capacitors
Series VJ HIFREQ Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 240pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance ±5% Voltage - Rated 25V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style	Series	VJ HIFREQ
Voltage - Rated Temperature Coefficient CoG, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Capacitance	240pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style COG, NPO OG, NPO	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style - O.057 (1.45mm)	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.057" (1.45mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
· ·		Report errors?

VJ0805D241JLXAR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D241JLXAR Payment Methods



















VJ0805D241JLXAR Shipping Methods













If you have any question about VJ0805D241JLXAR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com