

VJ0805D361MXXAT

VJ0805D361MXXAT Information

Heisener.com

Part Number VJ0805D361MXXAT

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 360PF 25V C0G/NP0 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0805D361MXXAT Specifications

Manufacturer Part Number V10805D361MXXAT Manufacturer Vishay Vitramon Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing -		
Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Manufacturer Part Number	VJ0805D361MXXAT
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Manufacturer	Vishay Vitramon
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Category	Capacitors
Series VJ HIFREQ Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)		Ceramic Capacitors
Capacitance 360pF Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Package	0805 (2012 Metric)
Tolerance ±20% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Series	VJ HIFREQ
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) Thickness (Max) 0.057" (1.45mm)	Capacitance	360pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) Thickness (Max) 0.057" (1.45mm)	Tolerance	±20%
Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Voltage - Rated	25V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) - 0.057" (1.45mm)	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.057" (1.45mm)	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	0.057" (1.45mm)
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

VJ0805D361MXXAT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D361MXXAT Payment Methods





















VJ0805D361MXXAT Shipping Methods













If you have any question about VJ0805D361MXXAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com