



VJ0805D561KXAAJ Information

Heisener.com

VJ0805D561KXAAJ Part Number Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 560PF 50V C0G/NP0 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0805D561KXAAJ Specifications

Manufacturer Part Number VJ0805D561KXAAJ Manufacturer Vishay Vitramon Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Manufacturer Part Number	VJ0805D561KXAAJ
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Category	Capacitors
Series VJ HIFREQ Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 560pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Package	0805 (2012 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Series	VJ HIFREQ
Voltage - Rated Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style	Capacitance	560pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) Thickness (Max) 1.25mm - Lead Spacing - Lead Style - COG, NPO OSG, NPO	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - RF, Microwave, High Frequency Failure Rate - Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.057" (1.45mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ0805D561KXAAJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D561KXAAJ Payment Methods



















VJ0805D561KXAAJ Shipping Methods













If you have any question about VJ0805D561KXAAJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com