

VJ0805D620JLBAC

VJ0805D620JLBAC Information

Heisener.com

Part Number VJ0805D620JLBAC

Manufacturer Vishay Vitramon

Category Capacitors
Ceramic Capacitors

Description CAP CER 62PF 100V C0G/NP0 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ0805D620JLBAC Specifications

Manufacturer Part Number Manufacturer Vishay Vitramon Category Capacitors Ceramic Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 62pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient Cog, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Sing / Parkage / Case 0805 (2012 Metric)		
Category Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 62pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Manufacturer Part Number	VJ0805D620JLBAC
Ceramic CapacitorsPackage0805 (2012 Metric)SeriesVJ HIFREQCapacitance62pFTolerance±5%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)	Manufacturer	Vishay Vitramon
Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 62pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Category	Capacitors
Series VJ HIFREQ Capacitance 62pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)		Ceramic Capacitors
Capacitance 62pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Package	0805 (2012 Metric)
Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Series	VJ HIFREQ
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Capacitance	62pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case O805 (2012 Metric)	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Voltage - Rated	100V
Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Temperature Coefficient	COG, NPO
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric)	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric)	Failure Rate	-
	Mounting Type	Surface Mount, MLCC
Circ / Dimension 0.070" L v. 0.040" W (2.00mm v. 1.25mm)	Package / Case	0805 (2012 Metric)
Size / Dimension 0.079 L x 0.049 W (2.00mm x 1.25mm)	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Height - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) 0.057" (1.45mm)	Thickness (Max)	0.057" (1.45mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

VJ0805D620JLBAC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D620JLBAC Payment Methods



















VJ0805D620JLBAC Shipping Methods













If you have any question about VJ0805D620JLBAC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com