

VJ0805D620MLAAP

VJ0805D620MLAAP Information

Heisener.com Order server carlo ber	 VJ0805D620MLAAP Vishay Vitramon Capacitors Ceramic Capacitors CAP CER 62PF 50V C0G/NP0 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VJ0805D620MLAAP Specifications

Manufacturer Part Number VJ0805D620MLAAP Manufacturer Vishay Vitramon Category Capacitors Category Ceramic Capacitors Package 0805 (2012 Metric) Series VJ HIFREQ Capacitance 62pF Tolerance ±20% Voltage - Rated 50V Operating Temperature 05C (21 2 % Cr Operating Temperature 05C ~ 125 °C Pactures High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Railure Rate - Mounting Type Surface Mount, MLCC Package / Case 0050° L x 0.049" W (2.00mm x 1.25mm) Size / Dimension 0.057" (1.45mm) Lead Spacing - Lead Spacing - Lead Spacing -		
CategoryCapacitorsPackage0805 (2012 Metric)SeriesVJ HIFREQCapacitance62pFTolerance±20%Voltage - Rated000 NP0Poreprature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsStrace Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.07°L x 0.049°W (2.00mm x 1.25mm)Hight - Seated (Max)-Hight - Seated (Max)-Hight - Seated (Max)0.057° (1.45mm)Lead Style-Lead Style-	Manufacturer Part Number	VJ0805D620MLAAP
Ceranic CapacitorsPackage0805 (2012 Metric)SeriesVJ HIFREQCapacitance62pFTolerance±20%Voltage - Rated50VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsSurface Mount, MLCCMounting Type0805 (2012 Metric)Size / Dimension0.057" (1.45mm)High Pacated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	Vishay Vitramon
Package0805 (2012 Metric)SeriesVJ HIFREQCapacitance62pFTolerance±20%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsF, Microwave, High FrequencyFailure Rate-Mounting TypeS05 (2012 Metric)Size / Dimension0.007" L x 0.049" W (2.00mm x 1.25mm)Fickness (Max).Height - Seated (Max).Lead Spacing.Lead Style.Starten Starten	Category	Capacitors
SeriesVJ HIFREQCapacitance62pFTolerance±20%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)High T- Seated (Max)-Hickness (Max)0.55° (1.45mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance62pFTolerance±20%Voltage - Rated50VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Hight - Seated (Max)-Lead Spacing-Lead Style-	Package	0805 (2012 Metric)
Tolerance±0%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spaing-Lead Style-Lead Style-	Series	VJ HIFREQ
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Size / Dimension-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style- </td <td>Capacitance</td> <td>62pF</td>	Capacitance	62pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Tolerance	$\pm 20\%$
Operating Temperature.55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.057" (1.45mm)Lead Spacing-Lead Style-State Style-<	Voltage - Rated	50V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Height - Seated (Max)-Start (Max)-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Features	High Q, Low Loss
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Applications	RF, Microwave, High Frequency
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.057" (1.45mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ0805D620MLAAP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ0805D620MLAAP Payment Methods





If you have any question about VJ0805D620MLAAP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com