

VJ1206Y152KBGAT4X

VJ1206Y152KBGAT4X Information



For Reference Only

Part Number VJ1206Y152KBGAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 1500PF 1KV X7R 1206

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1206Y152KBGAT4X Specifications

Manufacturer Part Number VJ1206Y152KBGAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1206 (3216 Metric) Series VJ OMID Capacitance 1500pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1206 (3216 Metric) Series VJ OMD Capacitance 1500pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Manufacturer Part Number	VJ1206Y152KBGAT4X
Package 1206 (3216 Metric) Series VJ OMD Capacitance 1500pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Manufacturer	Vishay Vitramon
Package 1206 (3216 Metric) Series VJ OMD Capacitance 1500pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Category	Capacitors
Series VJ OMD Capacitance 1500pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -		Ceramic Capacitors
Capacitance1500pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.132" L x 0.063" W (3.35mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-	Package	1206 (3216 Metric)
Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Series	VJ OMD
Voltage - Rated1000V (1kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.132" L x 0.063" W (3.35mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-	Capacitance	1500pF
Temperature Coefficient AyrR Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) Thickness (Max) 0.067" (1.70mm) Lead Spacing - X7R X7R X7R X7R - Size \ Dimension Ayrich Algebraic Algeb	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Voltage - Rated	1000V (1kV)
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Temperature Coefficient	X7R
Ratings - Graphications Boardflex Sensitive - Graphications Boardflex Sensitive - Graphications Surface Mount, MLCC - Graphications Size / Case Size / Dimension Size / Dimension Size / Dimension Size / Dimension Size / Case Seated (Max) - Graphication Size (Max) Seated (Max) - Graphication Size (Max) Seated (Max) Se	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Applications	Boardflex Sensitive
Package / Case 1206 (3216 Metric) Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.132" L x 0.063" W (3.35mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.067" (1.70mm) -	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.067" (1.70mm) Lead Spacing -	Size / Dimension	0.132" L x 0.063" W (3.35mm x 1.60mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.067" (1.70mm)
Lead Style -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

VJ1206Y152KBGAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1206Y152KBGAT4X Payment Methods



















VJ1206Y152KBGAT4X Shipping Methods













If you have any question about VJ1206Y152KBGAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com