

VJ1210A240KBLAT4X

VJ1210A240KBLAT4X Information



For Reference Only

Part Number VJ1210A240KBLAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 24PF 630V NP0 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1210A240KBLAT4X Specifications

Manufacturer Part Number V11210A240KBLAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 24pF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -		
Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 24pF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Manufacturer Part Number	VJ1210A240KBLAT4X
Package 1210 (3225 Metric) Series VJ OMD Capacitance 24pF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Manufacturer	Vishay Vitramon
Package 1210 (3225 Metric) Series VJ OMD Capacitance 24pF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Category	Capacitors
Series VJ OMD Capacitance 24pF Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -		Ceramic Capacitors
Capacitance24pFTolerance±10%Voltage - Rated630VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.073" (1.85mm)Lead Spacing-	Package	1210 (3225 Metric)
Tolerance ±10% Voltage - Rated 630V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Series	VJ OMD
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 630V COG, NPO COG, NPO Soft Termination, High Voltage Soft Termination,	Capacitance	24pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.073" (1.85mm)Lead Spacing-	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.073" (1.85mm)Lead Spacing-	Voltage - Rated	630V
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Temperature Coefficient	C0G, NP0
Ratings - Gardflex Sensitive Failure Rate - Gardflex Sensitive Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Gardflex Sensitive Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Applications	Boardflex Sensitive
Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.073" (1.85mm) -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.073" (1.85mm) Lead Spacing -	Size / Dimension	0.132" L x 0.098" W (3.35mm x 2.50mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.073" (1.85mm)
Land Styla	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

VJ1210A240KBLAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1210A240KBLAT4X Payment Methods





















VJ1210A240KBLAT4X Shipping Methods













If you have any question about VJ1210A240KBLAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com