

VJ1210A680JBRAT4X

VJ1210A680JBRAT4X Information



For Reference Only

Part Number VJ1210A680JBRAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 68PF 1.5KV NP0 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1210A680JBRAT4X Specifications

Manufacturer Part Number VJ1210A680JBRAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Manufacturer Part Number	VJ1210A680JBRAT4X
Package 1210 (3225 Metric) Series VJ OMD Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 1210 (3225 Metric) Series VJ OMD Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Category	Capacitors
Series VJ OMD Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 68pF Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Package	1210 (3225 Metric)
Tolerance ±5% Voltage - Rated 1500V (1.5kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Series	VJ OMD
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style - 100, NPO COG, NPO Soft Termination, High Voltage Soft Termination,	Capacitance	68pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style COG, NPO Og, NPO COG, NPO C	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.073" (1.85mm)Lead Spacing-Lead Style-	Voltage - Rated	1500V (1.5kV)
Features Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension United the Seated (Max) Thickness (Max) Lead Spacing Lead Style Soft Termination, High Voltage 8	Temperature Coefficient	C0G, NP0
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.073" (1.85mm) Lead Spacing - Lead Style -	Size / Dimension	0.132" L x 0.098" W (3.35mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.073" (1.85mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ1210A680JBRAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1210A680JBRAT4X Payment Methods



















VJ1210A680JBRAT4X Shipping Methods













If you have any question about VJ1210A680JBRAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com