

VJ1210Y333KBEAT4X

VJ1210Y333KBEAT4X Information



For Reference Only

Part Number VJ1210Y333KBEAT4X

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.033UF 500V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1210Y333KBEAT4X Specifications

| Manufacturer Part Number VJ1210Y333KBEAT4X Manufacturer Vishay Vitramon Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 0.033µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - Report errors? | | |
|--|--------------------------|---------------------------------------|
| Category Capacitors Package 1210 (3225 Metric) Series VJ OMD Capacitance 0.033µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Manufacturer Part Number | VJ1210Y333KBEAT4X |
| Package 1210 (3225 Metric) Series VJ OMD Capacitance 0.033μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Manufacturer | Vishay Vitramon |
| Package 1210 (3225 Metric) Series VJ OMD Capacitance 0.033μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Category | Capacitors |
| Series VJ OMD Capacitance 0.033µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | | Ceramic Capacitors |
| Capacitance 0.033μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Package | 1210 (3225 Metric) |
| Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Series | VJ OMD |
| Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-Lead Style- | Capacitance | 0.033μF |
| Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style | Tolerance | ±10% |
| Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.132" L x 0.098" W (3.35mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-Lead Style- | Voltage - Rated | 500V |
| Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Temperature Coefficient | X7R |
| Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style | Operating Temperature | -55°C ~ 125°C |
| Applications Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Features | Soft Termination, High Voltage |
| Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Applications | Boardflex Sensitive |
| Package / Case 1210 (3225 Metric) Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Failure Rate | - |
| Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Mounting Type | Surface Mount, MLCC |
| Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - - | Package / Case | 1210 (3225 Metric) |
| Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - | Size / Dimension | 0.132" L x 0.098" W (3.35mm x 2.50mm) |
| Lead Spacing - Lead Style - | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | 0.067" (1.70mm) |
| · | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

VJ1210Y333KBEAT4X Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1210Y333KBEAT4X Payment Methods



















VJ1210Y333KBEAT4X Shipping Methods













If you have any question about VJ1210Y333KBEAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com