

VJ1210Y681MXPAT5Z

VJ1210Y681MXPAT5Z Information



For Reference Only

Part Number VJ1210Y681MXPAT5Z

Manufacturer Vishay Vitramon

Category Capacitors

Ceramic Capacitors

Description CAP CER 680PF 250V X7R 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VJ1210Y681MXPAT5Z Specifications

Manufacturer Part Number VJ1210Y681MXPAT5Z Manufacturer Vishay Vitramon Category Capacitors Package 1210 (3225 Metric) Series VJ HVArc Guard? Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 1210 (3225 Metric) Series VJ HVArc Guard? Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Manufacturer Part Number	VJ1210Y681MXPAT5Z
Package 1210 (3225 Metric) Series VJ HVArc Guard? Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Manufacturer	Vishay Vitramon
Package 1210 (3225 Metric) Series VJ HVArc Guard? Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Category	Capacitors
Series VJ HVArc Guard? Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 680pF Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Package	1210 (3225 Metric)
Tolerance ±20% Voltage - Rated 250V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Series	VJ HVArc Guard?
Voltage - Rated250VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-Lead Style-	Capacitance	680pF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) Thickness (Max) 1.20067" (1.70mm) Lead Spacing - Lead Style	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.067" (1.70mm)Lead Spacing-Lead Style-	Voltage - Rated	250V
Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Features	High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1210 (3225 Metric) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1210 (3225 Metric)
Thickness (Max) 0.067" (1.70mm) Lead Spacing - Lead Style -	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.067" (1.70mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

VJ1210Y681MXPAT5Z Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VJ1210Y681MXPAT5Z Payment Methods





















VJ1210Y681MXPAT5Z Shipping Methods













If you have any question about VJ1210Y681MXPAT5Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com